

Micrófono Saramonic Lavalier Inalámbrico Blink 500 PROX B3 para iOS Conector Lightning (2.4 GHz)



Marca: Saramonic
Código: MIC-SMN-0043
Disponibilidad: En tránsito

Precio: \$204.00

Descripción

- Receptor estéreo de dos canales para cámaras y dispositivos móviles 2.4ghz
- Alta resolución de Audio de 16-bit / 48 kHz
- Latencia 8ms
- Estuche de carga portátil para transmisor y receptor com 3000mAh para cargar 2.5 veces los dispositivos (35 horas de operación)
- Pantalla OLED vívida tanto en el transmisor como en el receptor
- Modo de salida mono / estéreo seleccionable
- Puerto de Monitor de auriculares en tiempo real
- Entrada de micrófono y entrada de línea
- Emparejamiento fácil
- Micrófono de solapa y deadcat incluidos en el paquete
- Baterías internas duran hasta 10 horas
- Cargador a traves de puerto USB-C
- Conector Lightning para iOS
- Rango 100m

Sistema

Wireless Technology	Digital 2.4 GHz
Included Transmitters	2 x Clip-On with Microphone
Diversity	Non-Diversity
RF Channel Scanning	Auto-Scan
Max Operating Range	328' / 100 m (Line of Sight)
Max Transmitters per Band	18
Built-In Recorder	No
Timecode Support	No
Control App Support	No
Sample Rate/Resolution	48 kHz / 16-Bit
Latency	< 8 ms
Encryption	<i>None</i>
Modulation	GFSK
SNR	>84 dB
THD	0.1 %

Receptor

Receiver Type	Camera-Mount / Beltpack / Portable
Mounting Options	Belt Clip, Shoe-Mount (with Included Hardware)
Antenna	1 x Internal
Number of Audio Channels	2
Audio I/O	1 x 1/8" / 3.5 mm TRS Female Unbalanced Output 1 x 1/8" / 3.5 mm TRS Female Unbalanced Headphone Output
Audio Output Level	-16.5 dBu
Phantom Power Protection	<i>None</i>
Frequency Response	20 Hz to 20 kHz

Network I/O	<i>None</i>
Word Clock I/O	<i>None</i>
USB/Lightning Connectivity	1 x USB Type-C Female (Bus Power, Charging)
Standalone Audio Interface Capable	No
Power Requirements	Battery or Bus Power (USB)
Battery Type	1 x Built-In Rechargeable (Included, Not Replaceable)
Approx. Battery Life	10 Hours
Display & Indicators	1 x OLED (Battery Status, Data Transmission, Mute, Power, Recharging, Sync, Transmitter Battery Status)
Operating Temperature	32 to 122°F / 0 to 50°C
Storage Temperature	-4 to 131°F / -20 to 55°C
Dimensions	2.2 x 1.5 x 0.6" / 5.6 x 3.8 x 1.5 cm
Weight	1.1 oz / 31 g

Transmisor

Transmitter Type	Clip-On with Microphone
RF Output Power	< 10 mW
Audio I/O	1 x 1/8" / 3.5 mm TRS Female Unbalanced Input
Muting	Mute Switch
Audio Input Level	-20 to -42 dBV (at 0 dB Gain)
Auto-Level Control	No
Frequency Response	20 Hz to 20 kHz
Sync Method	Proprietary
Antenna	1 x Internal
Power Requirements	Battery or Bus Power (USB)
Battery Type	1 x Built-In Rechargeable (Included, Not Replaceable)
Approx. Battery Life	10 Hours
USB/Lightning Connectivity	1 x USB-C (Bus Power, Charging)
Display & Indicators	1 x OLED (Audio Level, Battery Status,

Operating Temperature	Mute, Power, Signal Strength) 32 to 122°F / 0 to 50°C
Storage Temperature	-4 to 131°F / -20 to 55°C
Dimensions	2.2 x 1.5 x 0.6" / 5.7 x 3.8 x 1.5 cm
Weight	1.1 oz / 30 g

Especificaciones

Características	
Alimentación	Batería Incorporada
Cableado	Inalámbrico
Para	Conector tipo Lightning (iOS)
Pattern	Omnidireccional
Rango	100m
Tipo de Conector	Lightning (iOS)
Tipo de Micrófono	Lavalier
Tipo de Pastilla	condensador

Product Gallery

Saramonic®
Sound Remarkable. 🎧



Saramonic®
Sound Remarkable. 🎧



Saramonic®
Sound Remarkable. 🎧



Saramonic®
Sound Remarkable. 🎧



Saramonic®
Sound Remarkable. 🎧

